



## Installation Instructions

Part No. 2305000

### Replacement Spring Kit

For Hurst Billet/Plus® Shifters with bias springs

Rev 02/26/2020

**WORK SAFELY!** For maximum safety, perform this installation on a clean, level surface and with the engine turned off. Place blocks or wedges in front of and behind both rear wheels to prevent movement in either direction.

**CAUTION:** To avoid any possibility of bodily injury or damage to vehicle, do not attempt installation until you are confident that the vehicle is safely secured and will not move.

#### INSTALLATION INSTRUCTIONS

1. Remove cover or console from shifter.
2. Place the shifter in Neutral.
3. Remove the (4) pan head Torx screws that secure the spring retainer plates.
4. Remove the spring retainer plates.
5. Remove the old inner and outer springs from the shifter housing.
6. Insert the new inner and outer springs in the housing.
7. Position the spring retainer plates over the new springs.
8. Apply high-strength thread locker (Permatex Red or equivalent) to the (4) pan head Torx screws and tighten them down evenly.
9. Torque the screws to 20-24 in-lbs.
10. Replace the console cover.

**IMPORTANT: RETAIN THESE INSTRUCTIONS FOR FUTURE REFERENCE**

#### Technical Service

Hurst Performance maintains a highly trained technical service department to answer your technical questions, provide additional product information and offer various recommendations.



**Hurst Performance Products**

(866) 464-6553

[www.hurst-shifters.com](http://www.hurst-shifters.com)